

Impact-R 4060




Features

The Impact-R 4060 series of computers are powered by Intel® based motherboards, delivering a compact and flexible computer platform.

- Intel® Skylake CPU architecture
- DDR4 Memory up to 64GB
- Supports 3 native displays simultaneously

Our production processes are controlled under ISO 9001 and every system undergoes a full diagnostic burn-in prior to shipment.

Dimensions



Sales: +44 (0) 1273 570 220 Admin: +44 (0) 1273 608 331 Fax: +44 (0) 1273 570 215 Website: www.amplicon.com Email: sales@amplicon.com

Impact-R 4060

Specifications

The information is believed to be accurate. However Amplicon Liveline Limited accepts no responsibility for any problems caused by errors and omissions. Specifications are subject to change without notice.

Hardware Specification	CPU: Intel® LGA1151 6 th generation Core™ i7/i5/i3, Pentium™ and Celeron™ Supports Intel® 14nm Chipset: Intel® Q170 Chipset Memory: 4 x DIMM - max 64GB DDR4 2133MHz non-ECC Dual channel architecture Graphics*: Integrated GPU: HDMI - max 4096*2160 @ 24Hz and 2560*1600 @ 60Hz Display port - max 1920*1200 @ 60GHz VGA - max 1920*1200 @ 60Hz LAN: RealTek® RTL8111H GbE	Mechanical	Design: EIA RS-310C 19" Rackmount Standard Construction: 1.2mm SECC Zinc-Coated Steel Security: Lockable front door Colour: Black (custom colours available for large orders) Dimensions: 483 x 177 x 573mm (19.0" x 7.0" x 22.6") Packaging Size: 590mm x 331mm x 750mm (23.2" x 13.0" x 29.5") Cooling: 3x 120mm ball bearing fan Air filter: removable (washable) Gross Weight: approximately 22 kg
Storage*2/3	Total Drive capacity: 6x 5.25" external, 1x 3.5" external, 1x 3.5" internal *Options for mSATA available	Environmental operation	Acoustic noise: Approximately 49dB(A) sound pressure at 23°C (typical) Temperature: 5 to 45°C (tested for extended operation up to 50°C) Humidity: 5 to 90% at 25°C non-condensing
System Expansion	1 x PCIe x16 slot (revision 3.0/2.0) 2 x PCIe x4 slot (revision 3.0/2.0) 4 x PCI slots 1 x mPCIe (full/half length) 1 x SIM card slot	Environmental storage	Temperature: -20 to 65°C Humidity: 5 to 90% at 25°C non-condensing
System Architecture	Industrial use motherboard	Certification	CE/UKCA Marked
Supported OS	Windows 7, Windows 8.1, Windows 10 (32 & 64 bit)		
External Interfaces	Front: 2 x USB 2.0/1.1 On/Off Switch, Reset Pwr/HDD LEDs Rear: 1 x PS/2 Keyboard 1 x PS/2 Mouse 4 x USB 3.0 1 x DP, 1 x HDMI, 1 x VGA 2 x Intel GbE RJ45 1 x RS232/422/485 DB9 2 Stack Audio		

Sales: +44 (0) 1273 570 220 Admin: +44 (0) 1273 608 331 Fax: +44 (0) 1273 570 215 Website: www.amplicon.com Email: sales@amplicon.com